

**LADY SHRI RAM COLLEGE FOR WOMEN
(UNIVERSITY OF DELHI)**

CORRIGENDUM

Sub: Technical changes in NIT.

Tender Reference Number	LSR/CCTV/2018-19/03
Tender ID	2019_DU_428440_1
Bid Submission End Date and time	04th Feb, 2019 (5:00 P.M.)
Technical Bid Opening Date and time	06th Feb, 2019 (11:00 A.M.)

All prospective bidders are requested to note change in NIT clause as follows. Same shall be signed & stamped along with NIT documents.

S.No.	Clause in NIT	Change in Clause of NIT
NIT/ BOQ S.No. 3 Sec B	Resolution 1920 × 1080 2 Megapixel 1/3” Progressive Scan CMOS Image Sensor Powerful	Standard Network IR PTZ incorporates a 4MP high performance, progressive scan CMOS sensor for full HD quality images up to 2592×1520 resolution, Image Sensor 1/2.8" progressive scan CMOS
	IR Range upto 50 meters Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR Color: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR,	IR Distance Up to 150m Min. Illumination Color: 0.05 Lux @ (F1.6, AGC ON), B/ W: 0 .01 Lux @ (F1.6 , AG C ON) IR: 0 Lux, WDR True WDR 120Db,
	Shutter Speed 1/3 s to 1/100,000 s, Slow Shutter supported,	Shutter Speed 1/1 s to 1/32000 s Zoom Speed Approx. 3s (optical lens, wide-tele),
	Digital Noise Reduction 3D DNR, WDR 20dB,	Digital Noise Reduction 3D
	Focal length 2.8 to 12 mm Motorized zoom Lens,	Focal Length 4.3 to 129mm
	Video Compression Main stream: H.265+/H.265/H.264+/H.264, Sub stream: H.265+/H.265/H.264+/H.264/MJPEG Third stream: H.265+/H.265/H.264+/H.264, Video Bit Rate 32 Kbps to 16 Mbps, Audio Compression G722.1/G711ulaw/G711alaw/G726/MP2L2,	Video Compression Main stream: H.265+/H.265/H.264+/H.264, Sub stream: H.265+/H.265/H.264+/H.264/MJPEG Third stream: H.265+/H.265/H.264+/H.264, Video Bit Rate 32 Kbps to 16 Mbps, Audio Compression G722.1/G711ulaw/G711alaw/G726/MP2L2
	Protocols TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour, ONVIF Supports PROFILE S, PROFILE G, IP 66,	1 * RJ 45 10/100 M Self Adaptive Ethernet Port Protocols TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour, ONVIF Supports PROFILE S, PROFILE G, IP 67
	Operating Conditions Temperature: -30 °C to +60 °C (-22 °F to +140 °F) Humidity: 95% or less (non-condensing), Power Supply 12 VDC ± 25%, PoE (802.3at)	Operating Conditions Temperature: -30 °C to +60 °C (-22 °F to +140 °F) Humidity: 95% or less (non-condensing), Power Supply 12 VDC ± 25%, PoE (802.3at)
	Power Consumption and Current 12 VDC, 1.2A, max. 14.5W PoE (802.3at, 42.5V to 57V), 0.5A to 0.1A, max. 16.5W Protection Level IP67, IK10 TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection	Power Consumption and Current 12 VDC, 1.2A, max. 14.5W PoE (802.3at, 42.5V to 57V), 0.5A to 0.1A, max. 16.5W Protection Level IP67, IK10 TVS 2000V Lightning Protection, Surge Protection and Voltage Transient Protection
WDR 120DB, 2.8-12 mm Manual Varifocal , DC12V ± 25%, PoE (802.3af)	33× Optical, Zoom Speed Approx. 3s (optical lens, wide-tele), Movement Range (Pan) 360° Continuous Rotate	
NIT/ BOQ S.No. 4 Sec B	16 Channel Standalone NVR (Qty 08)	32 Channel NVR Standalone (Qty 04)

The last date All the quantities will remain as per BOQ. Final Bill will be raised as per actual quantity installed/used

Any Additional work will be as per requirement. All other Terms & conditions will remain unchanged.